


- Can be installed vertically or horizontally
- Link light comes with a 1000mm power lead, a 500mm link lead, fixing screws and brackets
- For indoor use only, not to be used in bathrooms
- Point of sale full colour box packaging on every model



<b>Code</b>	T5-LED-14
<b>Description</b>	T5 LED Super Slim Link Light – 14 Watt – 1173mm – 90 LEDs – Natural White
<b>Size</b>	1173mm (L) x 22mm (H) x 30mm (W)
<b>Range</b>	Selectric T5 LED Super Slim Link Lights
<b>Colour</b>	White
<b>Material</b>	Polycarbonate body & diffuser
<b>Included</b>	Fixing kit & instructions
<b>Weight</b>	0.268kg
<b>Inner Carton Quantity</b>	1
<b>Inner Carton Weight</b>	0.438kg
<b>Outer Carton Quantity</b>	20
<b>Outer Carton Weight</b>	11kg
<b>Warranty</b>	3 years
<b>Guarantee</b>	30,000 hours
<b>Barcode</b>	5025117004616
<b>Commodity Code</b>	9405409000
<b>Standards</b>	EN 55015, EN 61000-3 & -4, EN 61547, EN 60598-1 & -2
<b>Notes</b>	<ul style="list-style-type: none"> <li>• This 14 Watt version is linkable up to a max of 8 units</li> <li>• Available in various colour temperatures and lengths enabling you to choose the perfect product for your chosen location</li> <li>• Other colour temperatures available: 6000K Cool White / 3000K Warm White</li> </ul>



<b>Wattage</b>	14W
<b>Lumens Delivered</b>	1190 lumens
<b>Luminaire efficacy</b>	85lm/w
<b>Colour Rendering Index min</b>	Ra80
<b>Correlated colour temperature</b>	4000K Natural White
<b>Input</b>	230V
<b>Hertz</b>	50Hz/60Hz
<b>Operating Temp</b>	-20°C-45°C
<b>Type of Dimming</b>	Non-dimmable
<b>Impact Strength</b>	IK08
<b>Protection Class / IP Rating</b>	IP20
<b>Wall Mounting?</b>	Yes
<b>Suspended Mounting?</b>	No
<b>Ceiling Mounting?</b>	Yes
<b>Built-in Mounting?</b>	No
<b>Surface Mounting?</b>	Yes
<b>Beam Angle</b>	120°
<b>Emergency Back-Up?</b>	N/A
<b>Maintained / Non-Maintained?</b>	N/A
<b>Driver</b>	Lifud
<b>LED Chips</b>	90 x Yuanlei LED chips
<b>Sensor</b>	N/A