



Code:	LG9099MB-USB
Description:	13 Amp USB Socket Outlets - 1 Gang Switched with 1 x USB Type A Port (2.1A)
Range:	Selectric Metal Clad
Colour:	Grey with white insert
Ingress Protection:	IP20
Material:	High grade steel with aluminium epoxy powder coating
Included:	Back box & M3.5 fixing screws
Weight:	0.36kg
Inner Carton Quantity:	10
Inner Carton Weight:	3.6 kg
Guarantee:	5 years
Barcode:	5025117004753
Commodity Code:	8536 699099
Standards:	BS 1363-2:2016+A1:2018 EN IEC 62368-1:2020+A11:2020, EN IEC 62680-1-1, EN IEC 61000-6-1:2019, EN IEC 61000-6-3:2021
Packaging:	Poly Bag with Euro Slot
ASTA Approval:	No
Notes:	<ul style="list-style-type: none"> • USB output – DC 5V 2.1 Amp • If the USB port exceeds 10.5W, the power supply will stop working • Overload protection shuts off output if the connected device draws too much power • Fault protection automatically cuts power during abnormal conditions and resets itself once the issue is removed • Thermal protection prevents overheating • 0.3A 50Hz +/- 3Hz • Surface mounting box included



Selectric reserves the right to withdraw, improve, or modify any design without prior notification.
Selectric cannot be held responsible for the incorrect application / installation of any product.